



PT-103

Tie-Wrap Tag



CONTENTS

1	PRODUCT DESCRIPTION	2
1.1	Specifications.....	2
1.2	Dimensions	3
1.3	Read Range.....	4
1.4	Environmental Specifications	4
1.5	Supported Services.....	5
1.6	Possible Applications	5
2	INSTALLATION INSTRUCTIONS	5
3	ATTACHMENT PHOTO'S.....	5
4	CONTACTING TROI LLC	6



PT-103



Tie-Wrap Tag

1 PRODUCT DESCRIPTION

The patent-pending **TROI PT-103 Tie-Wrap** RFID tags provides automatic identification and tracking capabilities never-before available in such a unique package designed for rugged or hazardous use-areas.

The plastic-covered tag is molded onto a tie-wrap and is designed to be mounted to any metallic surface by just securing the tie-wrap around it. The tag can withstand unprecedented high temperature (consistent temperatures of 150 degrees Centigrade), high pressure and severe environmental conditions.

1.1 SPECIFICATIONS

Device type	Passive RFID tag
Air interface protocol	UHF: EPCGlobal Class1Gen2 / ISO/IEC 18000-6C (-63) HF: EPCGlobal Class1Gen2 / ISO/IEC 18000-6B (-62)
Operational frequency	UHF: 865-869 MHz (EU), 902-928 MHz (US) HF : 13.56 MHz
IC options - UHF	Standard: Alien Higgs 3 (others on request) Optional: EM, Fujitsu, Impinj, NXP (others on request)
EPC memory - UHF	Standard: 128 bit Optional: Up to 240 bit
EPC memory content	Unique 96-bit number encoded
Extended memory - UHF	Standard: 512 bit
TID - UHF	Factory-programmed, non-changeable, unique 64-bit ID.
Read range - UHF	Real-world: 1 – 2 meters
Size	Standard tie length: 102 mm (4 inches) Tie material can be nylon or metal, and many lengths – contact us!
Tag material	Plastic covered tag mounted to either a metal or plastic tie-wrap
Tensile strength	Metal Tie-Wrap: Plastic Tie-wrap:
Applicable surfaces	Any material
Product RoHS compliant?	Yes
Standards compliancy	ATEX-compliant



PT-103

Tie-Wrap Tag




1.2 DIMENSIONS

Tie wrap: **L:** 140 mm (5.5 inches) x **W:** 3 mm (0.12 inches) x **H:** 0.8 mm (0.3 inches)

Tag body: **L:** 25 mm (1 inches) x **W:** 9 mm (0.35 inches) x **H:** 6 mm (0.2 inches)

NOTE: Pictures not to size

TOP VIEW



SIDE VIEW



Balance of page left blank



PT-103

Tie-Wrap Tag



1.3 READ RANGE

	UHF max read-range on metal with 4W EIRP
PT-103 (915 MHz)	660.4 cm / 260 inches (6.63 m / 21.75 feet)

The read range listed above was obtained from a lab test environment. Actual test results may be different. Testing in actual use environments is strongly recommended.

1.4 ENVIRONMENTAL SPECIFICATIONS

Operating temperature	-50°C to +150°C* (-58°F to 302°F)
Temperature Cycling Test	150 deg C, continuous for 30-days
IP classification	IP69K
Weather resistance	Excellent, including UV-resistance and sea water immersion
Chemical resistance	No physical or performance changes in: <ul style="list-style-type: none"> - Salt water - NaOH (depending on concentration) - Sulfuric acid (depending on concentration) - Motor oil (tested in 168 hour exposure) Generally good against: <ul style="list-style-type: none"> - Most solvents - Most acids and bases

* **NOTE:** The RFID tag will not be functional if it is left at the maximum indicated temperatures such that the internal soak temperature exceeds +80 deg C. The RFID tag itself will (resume) function between -50 deg C and +80 deg C.

Balance of page left blank



PT-103

Tie-Wrap Tag



1.5 SUPPORTED SERVICES

- Tag pre-encoding
- Laser marking

For further details, please contact **TROI LLC**.

1.6 POSSIBLE APPLICATIONS

Any surface

Returnable containers, canisters, pallets, pipes, high value items, aerospace applications, military applications, etc.

2 INSTALLATION INSTRUCTIONS

Wrap the tie-wrap around the surface, insert the tail of the tie-wrap into the head of the tie-wrap and firmly pull the tie-wrap to secure the tag to the object – done!

3 ATTACHMENT PHOTO'S

The photo's below show a PT-103 attached to one of the power lines inside an electrical distribution box (see red circles).





PT-103

Tie-Wrap Tag



4 CONTACTING TROI LLC

For additional information and technical support contact:

TROI LLC

311 Drury Lane
Mauldin SC 29662
PH: 864-228-9096

pat@troirfid.com
www.troirfid.com

ADVISORY

Although any information, recommendations, or advice contained herein is given in good faith, **TROI LLC** makes no warranty or guarantee, express or implied, (i) that the results described herein will be obtained under end-use conditions, or (ii) as to the effectiveness or safety of any design incorporating its products, materials, services, recommendations or advice. Except as provided in **TROI LLC** standard conditions of sale, **TROI LLC** and its representatives shall in no event be responsible for any loss resulting from any use of its materials, products or services described herein.

---END---