



RS-101

Large Pipe & Cylinder Rubber Tag



CONTENTS

1	PRODUCT DESCRIPTION	2
1.1	Specifications	2
1.2	Dimensions	3
1.3	Read Range	4
1.4	Environmental Specifications	4
1.5	Supported Services	5
1.6	Possible Applications	5
1.7	Pictures	5
2	CONTACTING TROI LLC	6



RS-101

Large Pipe & Cylinder Rubber Tag



1 PRODUCT DESCRIPTION

The patented (US Patent # 7,928,922) **TROI RS-101 Large Pipe & Cylinder Rubber** RFID tag provides automatic identification and tracking capabilities never-before available in such a unique package designed for rugged or hazardous use-areas.

The rubber-covered tag is designed to be mounted to any metallic surface by either screwing or bolting the tag down, or using dual side bands or ties (steel or nylon) to secure it to the object. The **RS-101** can withstand unprecedented high temperature (consistent temperatures of 160 degrees Centigrade), high pressure and severe environmental conditions.

1.1 SPECIFICATIONS

Device type Passive RFID tag	UHF (Ultra High Frequency band)
Air interface protocol	EPCGlobal Class1Gen2 / ISO/IEC 18000-6C
Operational frequency	865 - 928 MHz
IC options	Standard: Alien Higgs 3 (others on request) Optional: EM, Fujitsu, Impinj, NXP (others on request)
EPC memory size	Standard: 128 bit Optional: Up to 240 bit
EPC memory content	Unique 96-bit number encoded
Extended memory	Standard: 512 bit
TID	Factory-programmed, non-changeable, unique 64-bit ID.
Read range	Real-world: 1 – 2 meters Lab environment: 7 meters
Applicable surfaces	Any metallic material
Tag material	HVP rubber
Tensile strength	2500 psi minimum
Durometer	Shore A 60-70
Elongation	400% minimum
Durometer	Shore A 60-70
Drop test to asphalt	2 meters with 5 Kg's attached; 250+ times (competition fails at 20) 2 meters with 8 Kg's attached; 150+ times (competition fails immediately) 2 meters with 18Kg's attached; 25+ times (competition fails immediately)
Standards compliancy	ATEX-compliant
Product RoHS compliant?	Yes
US Patent Number	7,928,922



RS-101

Large Pipe & Cylinder Rubber Tag




1.2 DIMENSIONS

Long: 150 mm (5.9 inches) **Wide:** 16 mm (0.63 inches) **High:** 9 mm (0.35 inches)

Hole Diameter: 6 mm (0.24 inches) **NOTE:** Hole does not go all the way through tag from factory.


PLAN VIEW




SIDE VIEW – showing banding slots



SIDE VIEW – showing banding slot



END VIEW – showing mounting hole





RS-101

Large Pipe & Cylinder Rubber Tag



1.3 READ RANGE

	UHF max read-range on metal with 4W ERP
RS-101 (915 MHz)	660.4 cm / 260 inches (6.63 m / 21.75 feet)

The read range listed above was obtained from a lab test environment. Actual test results may be different. Testing in actual use environments is strongly recommended.

1.4 ENVIRONMENTAL SPECIFICATIONS

Operating temperature	-50°C to +160°C* -50°F to +320 °F*
Temperature Cycling Test	85 deg C continuous for 30-days - with no negative affect 85 deg C / -25 deg C shock for 7 days - with no negative affect 125 deg C @ 100% RH continuous for 7 days - with no negative affect 160 deg C continuous for 7 days - tag becomes brittle, but functions OK 200 deg C @ 100% RH for 24 hours – with no negative affect
IP classification	IP69K EN 62262 IK-25 - Complete protection against dust - Protection against continuous immersion in water
Weather resistance	Excellent, including UV-resistance and sea water immersion
Pressure resistance	RFID tag tested to 30,000 PSI for 30 days
Chemical resistance	No physical or performance changes in: - Salt water - NaOH (depending on concentration) - Sulfuric acid (depending on concentration) - Motor oil (tested in 168 hour exposure) Generally good against: - Most solvents - Most acids and bases

* **NOTE:** The RFID tag will not be functional if the tag is left at the maximum indicated temperatures such that the internal soak temperature exceeds +80 deg C. The RFID tag itself will (resume) function between -50 deg C and +80 deg C.



RS-101

Large Pipe & Cylinder Rubber Tag



1.5 SUPPORTED SERVICES

- Tag pre-encoding

For further details, please contact **TROI LLC**.

1.6 POSSIBLE APPLICATIONS

Metal surfaces

Metal valves, metal returnable containers, metal pallets, metal pipes, high value metal items, aerospace applications, military applications, etc.

1.7 PICTURES

The picture below shows stainless steel tie wraps inserted through the slots on both ends of the tag.



The picture below shows a close-up of the stainless steel tie wrap placed through the slot.





RS-101

Large Pipe & Cylinder Rubber Tag



2 CONTACTING TROI LLC

For additional information and technical support contact:

TROI LLC

311 Drury Lane
Mauldin SC 29662
PH: 864-228-9096

pat@troirfid.com
www.troirfid.com

ADVISORY

Although any information, recommendations, or advice contained herein is given in good faith, TROI LLC makes no warranty or guarantee, express or implied, (i) that the results described herein will be obtained under end-use conditions, or (ii) as to the effectiveness or safety of any design incorporating its products, materials, services, recommendations or advice. Except as provided in TROI LLC standard conditions of sale, TROI LLC and its representatives shall in no event be responsible for any loss resulting from any use of its materials, products or services described herein.

---END---